

The Chief Administrator,
H.S.A.M.Board,
Panchkula.

To

All the S.Es/E.Es,
H.S.A.M.Board,
In the State of Haryana.

Memo No. 15810-35

Dated:-

07-10-2010

Subject: Use of earth in the construction of link roads in the State of Haryana by H.S.A.M. Board.

At present, Board is allowing earth work in construction & special repair of link roads from both sides of consolidation path i.e. from adjoining fields with a lead of 15 meters and in inhabited area, lead of 1 K.M. is being allowed. In view of the difficulties being faced in the field, as earth is not being allowed by the adjoining land owners, the matter has been reconsidered by the Board/Govt. and it has been decided to allow earth from a lead of 2 K.M. with the following criteria:-


1. No earth shall be taken from the width of available consolidation path (Right of Way) and up to 50 meters from the outer boundary of consolidation path (ROW) on both sides.
2. A lead of 2 K.M. should be considered for estimation, analysis, financial comparison etc. only.
3. The item for compensation for earth, if taken from private land may also be taken in the Rough Cost Estimate.
4. Provisions of item of earth work in DNIT should be made as under:-
"Earth work on embankment in all kind of soil with minimum CBR value 5% with any lead and lift including dressing and laying in layers not exceeding 25 cm. loose thickness including watering and rolling to desired density inclusive of all sort of compensation of land/earth, as per MORT & H specifications."
5. The payment of earth work in case of construction of link roads &

Raising of roads will be released as given below:-

- (i) 80% of quoted rate will be given for the quantity of earth work executed at site as per item No. 4 given above.
- (ii) Another 10% of quoted rates for quantity of already executed earth work will be released after laying & WBM of Grade-I layer of stone metal for the specific K.M.
- (iii) Remaining 10% of quoted rates on the quantity of already executed earth work will be released after laying & WBM of Grade-II layer of stone metal for the specific K.M.


The above provisions except Sr.No. 3 be made in DNIT to be approved, henceforth.

Endst. No. 15836-42


Executive Engineer (R)
For Chief Administrator ✓
Dated 7.10.10

A copy of the above is forwarded to the following for information and necessary action:-

1. The P.S. to C.A./EIC, H.S.A.M.Board, Panchkula.
2. The P.S. to C.E.(R),/C.E. (M) HSAMBoard, Panchkula.
3. The SDOs (R)/SDO (M), HSAMBoard, Panchkula.
4. The CHD(R), HSAMBoard, Panchkula.


Executive Engineer (R)
For Chief Administrator ✓